
1. Product and Company Identification

Identity (as used on label & list): **EasyDECON Part 2**
Product Description: Hydrogen Peroxide and Water
Intended Use: Disinfectant, Mildewstat, Virucide, only for use when added to EasyDECON Part 1

Supplier Details: EFT Holdings, Inc.
1275 Rock Creek Circle
Lafayette, CO 80026
303-309-6309

Emergency Telephone
Number (with hours of operation) 1-800-424-9300 (24/7)

2. Hazards Identification

Hazardous Classification:

Pictogram:



Signal word: Danger

Hazard Statement: Causes skin burns, can cause irreversible eye damage, harmful if swallowed or inhaled

Under conditions of intended use this product is not considered hazardous and does not pose a risk to health.

Overview; Ingredients not listed as a carcinogen by IARC, NTP, or OSHA

DOT Hazard Class: Not Applicable

Threshold Value Limit (TLV): Not Determined

Signs and Symptoms of Exposure:

Eyes Will cause irritation and inflammation characterized by redness, watering, and itching; depending on length of exposure, solution concentration and first aid measures provided.

Skin Causes skin irritation characterized by reddening. Prolonged contact with product may cause discomfort, no adverse effects expected from absorption of material through skin.

Ingestion Not expected to be a primary route of exposure, will produce gastrointestinal discomfort.

Inhalation Not expected to be a primary route of exposure, vapors or mists in unusually high concentration, in poorly ventilated areas may cause irritation of nose and throat characterized by coughing.

3. Composition/ Information on Ingredients

Component	CAS-No.	%Wt.
Hydrogen Peroxide	7722-84-1	7.9
Water	7732-18-5	92.1

June 1, 2015

4. First Aid Measures

- Inhalation:** Remove to fresh air. If irritation persists, seek medical attention. If breathing has stopped, assist ventilation with a mechanical device or use rescue breathing with a pocket mask.
- Skin:** Wash skin with soap and water. Seek medical attention if irritation occurs and persists.
- Eyes:** Immediately flush with water for 15 minutes, lifting upper and lower lids intermittently. If eye irritation persists, seek medical attention.
- Ingestion:** If swallowed, get immediate medical attention or advice. If victim is conscious and able to swallow, give large amounts of water. Do not give anything by mouth to the person who is unconscious or convulsing. Do not induce vomiting unless directed by a physician.

5. Fire Fighting Measures

Flash Point	Not Applicable
Auto Ignition Temperature:	Not Applicable
Flammable Limits	Not Applicable
Classification	Not Flammable
Extinguishing Media	Water

Special Fire Fighting Procedures: NFPA Code: Health 1, Fire 0, Reactivity 1, Special OX

Use water spray to cool fire-exposed surfaces to prevent over-pressure of containers and to protect personnel. Use air-supplied breathing equipment for enclosed areas.

Product is non-combustible. On decomposition from excessive heat it will release oxygen which may intensify fire.

6. Accidental Release Measures

- Containment Procedures** Stop flow of material if without risk. Dike spill with inert material and dilute with water. Hold until Hydrogen Peroxide decomposes. Block any potential routes to water systems, sewers, streams, lakes, etc.
- Clean-Up Procedures** Wear appropriate protective equipment and clothing. Combustible materials exposed to TurnoutClear Part 2 should be rinsed with water to remove Hydrogen Peroxide.
- Evacuation Procedures** Keep unnecessary personnel away.

7. Handling and Storage

- Handling Procedures** Avoid contact with skin and eyes. Observe good industrial hygiene practices and wash thoroughly after handling.
- Technical Measures** Work practices should minimize contact. EasyDECON Part 2 should be stored in vented containers. Avoid excessive heat and contamination. Contamination may cause decomposition and generation of Oxygen gas that may overpressure container. Do not return unused EasyDECON Part 2 to original container. Utensils for handling EasyDECON Part 2 should only be made of glass, stainless steel, aluminum, or plastic.
- Technical Precautions** Local exhaust is normally not required unless the process produces a mist.
- Storage Procedures** Store in closed vented original container, in well ventilated place, out of direct sunlight, away from combustibles. Prevent from freezing. If frozen, move to warm area.

8. Exposure Controls/ Personal Protection

- Ventilation Engineering Controls:** Ventilation should effectively remove and prevent any buildup of any vapor or mist generated from the use of this product.

June 1, 2015

Personal Protection Equipment (PPE)***Respiratory Protection:***

If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH/MSHA rated self-contained breathing apparatus should be used. Do not use a mask containing oxidizable elements.

Skin Protection:

Use Impervious gloves. Use of impervious apron and boots (neoprene, nitrile, pvc) are recommended.

Eye/Face Protection:

Wear safety glasses, chemical goggles or a full face shield.

Other Protective Clothing / Equipment:

Avoid exposure of cotton and leather clothing and footwear to this product. If exposed rinse well before allowing to dry.

9. Physical and Chemical Properties

Physical State	Liquid
Appearance and Color	water white liquid
Boiling Point	216 ^o F, 102 ^o C
Odor	odorless
Vapor Pressure @30 ^o C (mmHg)	31
Vapor Density (air=1) less than	equivalent to water
Solubility in Water	Complete
Specific Gravity (H ₂ O=1)	1.06
Burning Properties	Not applicable
Flammability	Not Flammable
Explosive Properties	Not Explosive
Flashpoint	Not applicable
Auto-ignition temperature	Not applicable
pH of Product	2.5-3.5
Evaporation Rate (Butyl Acetate=1)	<1
Viscosity	≈ water

10. Stability and Reactivity

<i>Chemical Stability:</i>	This is a chemically stable material. Excessive heat or contamination could cause product to become unstable.
<i>Conditions to Avoid:</i>	Excessive heat or contamination
<i>Materials to Avoid:</i>	Reducing agents, iron, copper alloys
<i>Hazardous Decomposition or Byproducts:</i>	Oxygen which will support combustion.
<i>Hazardous Polymerization</i>	Will not occur.

11. Toxicological Information

Eyes	Will cause irritation and conjunctivitis depending on length of exposure, solution concentration and first aid measures provided.
Skin	Prolonged contact with product may cause discomfort, no adverse effects expected from absorption of material through skin
Ingestion	Not expected to be a primary route of exposure. Rat oral LD ₅₀ (of mixed Part 1@49%, Part 2@49%, Part 3@2%) is greater than 5000milligrams/kilogram of body weight. Rat oral LD ₅₀ of Part 2 alone is greater than 5000milligrams/kilogram of body weight.
Inhalation	Vapors or mists in unusually high concentration, in poorly ventilated areas may cause irritation of nose and throat.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

June 1, 2015

12. Ecological Information

The product is not expected to be hazardous to the environment.

Mobility: This product is soluble in water and will spread in water systems

Degradability: The rate of degradation has ranges from 8 hr. to 20 days in water, 10 – 20 hours in air, and minutes to hours in soil depending upon microbiological activity and metals content.

13. Disposal Considerations

Waste Material Disposal of in accordance with Local, State and Provincial Environmental Regulations. May be diluted, allowing time for decomposition and discharged to suitable treatment system.

Treat container as residue.

14. Transport Information

Not Regulated

15. Regulatory Information

DOT Hazard Class: Not regulated

EPA Hazardous Substances: None

SARA 311/312 Hazards: Immediate (Acute) Health Hazard, Fire

TPQ None

SARA Title III: none

Governmental Inventory Status: All components comply with TSCA, DSL, AICS, NZIoC, ENCS, KECI, PICCS and IECSC.

16. OTHER INFORMATION

US NFPA Codes	Health	Fire	Reactivity	Special OX
	1	0	1	
HMIS Codes	Health	Fire	Reactivity	PPE Section 8
	1	0	1	

THE INFORMATION PRESENTED IN THIS SAFETY DATA SHEET (SDS) WAS PREPARED BASED ON DATA THAT WE BELIEVE IN OUR GOOD FAITH JUDGEMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS", AND INTELAGARD/EFT HOLDINGS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE.

THIS SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGEMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, INTELAGARD/EFT HOLDINGS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE OR FOREIGN LAWS. INTELAGARD/EFT HOLDINGS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS SDS/MSDS AVAILABLE TO YOUR EMPLOYEES.